

BRTNG11WSS3P Technical Specifications																		
Power source (KVA)	Power Supply (V)	Recommended IMM (T)	Traverser Stroke	Traverser Stroke (mm)	Crosswise Stroke (mm)	Vertical Stroke (mm)	Stand-by station (mm)	Max loading (Kg)	Cycle time (s)	Dry take out time(s)	Arm model	Model of EOAT	Angel	Working air pressure (MPa)	Air consumption (N-l /cycle)	Positioning accuracy (mm)	Complete machine size (mm)	Net weight (Kg)
3.2	220	250-480	AC servo motor	1700	700	1150	219	2	4.07	0.68	Single arms and telescopic type	2 suction 2 fixtures	90°	0.5-0.6	3.2	±0.05	2514.5*1272.5*1482	330
transverse				Crosswise					Obverse arm					Deputy arm				
Transverse electrical machines	Reducer	Slide rail	Gear rack / Belt	Electrical machines	Reducer	Slide rail	Gear rack / Belt	air cylinder	Electrical machines	Reducer	Slide rail	Gear rack / Belt	Air cylinder	electrical machines	Reducer	Slide rail	Gear rack /Belt	Air cylinder
1000W	750W 1:5	25mm	gear rack: 20mm	750W	750W 1:5	20mm	gear rack: 20mm	\	1000W	750W 1:5	15mm 20mm	Belt: 20mm gear rack: 20mm	\	\	\	\	\	\

